10/088329

JC10 Rec'd PCT/PTO 1 3 MAR 2002

I 3 MAR 2002 PATENT

S/N unknown

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:

OHTA et al.

Docket No.:

10873.881USWO

Serial No.:

unknown

Filed:

concurrent herewith

Int'l Appln No.:

PCT/JP01/05949

Int'l Filing Date:

July 9, 2001

Title:

LIQUID CRYSTAL DISPLAY DEVICE USING OCB CELL AND

DRIVING METHOD THEREOF

CERTIFICATE UNDER 37 CFR 1 10

'Express Mail' mailing label number: EV 036304644 US

Date of Deposit: March 13, 2002

I hereby certify that this correspondence is being deposited with the United States Postal Service 'Express Mail Post Office To Addressee' service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Name: Chris Stordahl

PRELIMINARY AMENDMENT

Box PCT Assistant Commissioner for Patents Washington, D.C. 20231

Dear Sir:

In connection with the above-identified application filed herewith, please enter the following preliminary amendment (marked-up copy attached):

IN THE SPECIFICATION

A courtesy copy of the present specification is enclosed herewith. However, the World Intellectual Property Office (WIPO) copy should be relied upon if it is already in the U.S. Patent Office.

IN THE CLAIMS

Please amend the following claims:

- 6. (Amended) The method for driving a liquid crystal display device according to claim 3, wherein when it is judged that the first period needs to be set, a voltage Vsup to be applied in a next frame is set to be of a level not less than a voltage Vsup applied in an immediately preceding frame, while when it is judged that the first period does not need to be set, a voltage Vsup to be applied in a next frame is set to be of a level not more than a voltage Vsup applied in an immediately preceding frame.
- 8. (Amended) The method for driving a liquid crystal display device according to claim 3, wherein when it is judged that the first period needs to be set, a first period to be set in a next frame is set to be not less than a length of a first period set in an immediately preceding frame, while when it is judged that the first period does not need to be set, a first period to be set in a next frame is set to be not more than a length of a first period set in an immediately preceding frame.

Please add the following new claims:

21. (New) The method for driving a liquid crystal display device according to claim 4, wherein when it is judged that the first period needs to be set, a voltage Vsup to be applied in a next frame is set to be of a level not less than a voltage Vsup applied in an immediately preceding frame, while when it is judged that the first period does not need to be set, a voltage Vsup to be applied in a next frame is

set to be of a level not more than a voltage Vsup applied in an immediately preceding frame.

22. (New) The method for driving a liquid crystal display device according to claim 4, wherein when it is judged that the first period needs to be set, a first period to be set in a next frame is set to be not less than a length of a first period set in an immediately preceding frame, while when it is judged that the first period does not need to be set, a first period to be set in a next frame is set to be not more than a length of a first period set in an immediately preceding frame.

REMARKS

The above preliminary amendment is made to remove multiple dependencies from claims 6 and 8.

Applicants respectfully request that the preliminary amendment described herein be entered into the record prior to calculation of the filing fee and prior to examination and consideration of the above-identified application.

If a telephone conference would be helpful in resolving any issues concerning this communication, please contact Applicants' primary attorney-of record, Douglas P. Mueller (Reg. No. 30,300), at (612) 371.5237.

Respectfully submitted,

MERCHANT & GOULD P.C. P.O. Box 2903

Minneapolis, Minnesota 55402-0903

(612) 332-5300

Dated: March 13, 2002

Douglas P. Mueller

Reg. No. 30,300

DPM/tvm

MARKED-UP COPY

- 6. (Amended) The method for driving a liquid crystal display device according to claim 3 [or 4], wherein when it is judged that the first period needs to be set, a voltage Vsup to be applied in a next frame is set to be of a level not less than a voltage Vsup applied in an immediately preceding frame, while when it is judged that the first period does not need to be set, a voltage Vsup to be applied in a next frame is set to be of a level not more than a voltage Vsup applied in an immediately preceding frame.
- 8. (Amended) The method for driving a liquid crystal display device according to claim 3 [or 4], wherein when it is judged that the first period needs to be set, a first period to be set in a next frame is set to be not less than a length of a first period set in an immediately preceding frame, while when it is judged that the first period does not need to be set, a first period to be set in a next frame is set to be not more than a length of a first period set in an immediately preceding frame.